Machine Translated by Google

TROUSERS

MOD-A-18



MOD-A-18



MOD-A-18





DESCRIPTION MOD-A-18

- High-waisted trousers, with a loose line around the lap thigh and knee, tight at the bottom.
- Length above the ankle.
- Front and back darts.
- Pockets cut on the front and applied on the back.
- Concealed front zip.
- Strap with visible button and under closure with automatic. (You can make a buttonhole).
- Bottom of the trousers finished with bias.



VERY IMPORTANT FOR THE REALIZATION OF THE MODEL IS TAKING THE MEASUREMENTS.

In the MEASUREMENTS page, selecting **"Show dummy for measures",** a dummy is displayed.

Selecting a box for entering measurements, for example Person Height, indicates how to correctly take this height.

Your Measurements must be entered as requested, then it is the TittiCad program that processes them so that the original proportions of the model chosen by you adapt to your measurements.

THE MOD-A-18 IS COMPOSED OF THE FOLLOWING PARTS:

N.1 FRONT. Once on the double fabric.

#2 BEHIND. Once on the double fabric.

N.3 SIDE PANEL. Once on the double fabric.

N.4 POCKET BAG. Once on the double fabric.

N.5 HALF STRAP. Once on the fabric fold.

N.6 APPLIED POCKET. Once on the double fabric.

Note:

The pattern already includes seam allowances.

MATERIAL REQUIRED FOR THE REALIZATION OF THIS MODEL

The fabric used for the model in the photo is slightly stretch jeans.

- Recommended fabric: denim, cotton.
- **QUANTITY** see following page.
- Sewing machine thread.
- Zipper, 18 cm long.
- Button diameter 18 mm.
- Automatic button diameter 1.5 mm.
- Bias tape to finish trouser bottoms.
- Reinforcing thermo-adhesive fabric for strap
 - 15 cm high 140 cm.

Being a made-to-measure model, it is not possible to indicate the right quantity for all the materials required.

You must be the one to measure it appropriately.

PATTERN ON THE FABRIC AND QUANTITY OF REQUIRED CLOTH

There are 2 possible cases, depending on whether you are using the TittiCad Program (installed on your PC), or the Online Pattern Making Service (present on the website www.titticad.com):

- TittiCad program: By

opening the PRINT page and selecting the Arrangement on fabric item from the "List of Available Prints",

a suggestion is displayed on how to position the model on the fabric.

- Online Patterns of www.titticad.com: After

entering the measurements and requesting the Free Preview, it is shown at the bottom of the page **Arrangement on fabric and required fabric length.**

The vertical arrow indicates the quantity of fabric required, while the horizontal arrow indicates the width of the fabric, it can be double fabric (when 75cm is indicated) or single fabric (when 150cm is indicated).

It is recommended to always take a little more (10-15 cm)

PACKAGING TIPS

Pattern preparation

How to assemble TittiCad pattern.

First steps in the packaging

2-3 Things to know about fabric before placing pattern on fabric.

How to place pattern on fabric.

Mark the outline of the pattern and assemble a front with a back.

Specific video tutorials for this model

Sew simple darts.

Jeans-type pocket packaging.

Packaging Applied Pocket.

How to put together the Front Pant with the Back.

Pack hidden zipper without flap flap.

Apply waist strap to a pant (skirt)

Strap closure with button and Automatic, without buttonhole.

How to apply thermoadhesive canvas.

How to apply bias tape to the bottom of trousers.

For all the video tutorials on the pack, click the link below:

www.titticad.com/package