## **SHORT JACKET**

### **MOD-A-22**



### **MOD-A-22**





### **MOD-A-22**

### **DESCRIPTION MOD-A-22**

Short jacket at the waist.

Soft fit.

Pockets inserted into the seam.

Three quarter sleeves, with cuff.

## VERY IMPORTANT FOR THE REALIZATION OF THE MODEL IS TAKING THE MEASUREMENTS.

In the MEASUREMENTS page, selecting "Show dummy for measures", a dummy is displayed.

Selecting a box for entering measurements, for example Person Height, indicates how to correctly take this height.

Your Measurements must be entered as requested, then it is the TittiCad program that processes them so that the original proportions of the model chosen by you adapt to your measurements.

# THE MOD-A-22 IS COMPOSED OF THE FOLLOWING PARTS:

- N.1 FRONT. Once on the double fabric.
- N.2 FRONT. Once on the double fabric.
- N.3 FRONT. Once on the double fabric.
- N.4 FRONT. Once on the double fabric.
- #5 FRONT. Once on the double fabric.
- N.6 FLAP. Twice on double fabric.
- N.7 FRONT PANEL. Once on the double fabric.
- N.8 POCKET. Once on the double fabric.
- N.9 POCKET. Once on the double fabric.
- #10 BEHIND. Once on the fabric fold.
- #11 BEHIND. Once on the fabric fold.
- #12 **BEHIND.** Once on the double fabric.
- N.13 BOTTOM BAND. Twice on the fabric fold.
- N.14 BEHIND THE PANEL. Once on the fabric fold.
- N.15 SLEEVE. Once on the double fabric.
- N.16 SLEEVE. Once on the double fabric.
- N.17 CUFF. Once on the double fabric.

#### Note:

The pattern already includes seam allowances.

# MATERIAL REQUIRED FOR THE REALIZATION OF THIS MODEL

The fabric used for the model in the photo is slightly stretch jeans.

- Recommended fabric: Cotton with or without elastane.
- QUANTITY see following page.
- Sewing machine thread.
- Bias tape for finishing pockets and facings.

Being a made-to-measure model, it is not possible to indicate the right quantity for all the materials required. You will have to measure them appropriately.

## PATTERN ON THE FABRIC AND QUANTITY OF REQUIRED CLOTH

There are 2 possible cases, depending on whether you are using the TittiCad Program (installed on your PC), or the Online Pattern Making Service (present on the website www.titticad.com):

 TittiCad program: By opening the PRINT page and selecting the Arrangement on fabric item from the "List of Available Prints",

a suggestion is displayed on how to position the model on the fabric.

Online Patterns of www.titticad.com: After
entering the measurements and requesting the Free
Preview, it is shown at the bottom of the page
Arrangement on fabric and required fabric length.

The vertical arrow indicates the quantity of fabric required, while the horizontal arrow indicates the width of the fabric, it can be double fabric (when 75cm is indicated) or single fabric (when 150cm is indicated).

It is recommended to always take a little more (10-15 cm)

#### **PACKAGING TIPS**

#### **Pattern preparation**

r attern proparation
How to assemble TittiCad pattern.
First steps in the packaging
2-3 Things to know about fabric before placing pattern on fabric.
How to place pattern on fabric.
Mark the outline of the pattern and assemble a front with a back.
Specific video tutorials for this model
MOD-A-22 Model parts assembly sequence.
Pocket in the seam.
Two ways to finish facing edge with bias.
For all the video tutorials on the pack, click the link below:

www.titticad.com/package