SHORT JACKET

MOD-A-49



MOD-A-49



MOD-A-49

DESCRIPTION MOD-A-49

Short jacket at the waist.

Darts at the back at the waist, darts on the front under the hollow to shape the breast.

Four-fifths sleeves, flared at the bottom and enriched with high cuff.

The cuff was placed on the straight weft thread so as to obtain a play of lines in contrast with the rest of the jacket.

Detail of the bottom of the jacket, used edge outwards and also like the exploited cuff the straight thread of the plot.

The seam allowances of the sides and shoulders, finished with stitched seam on the reverse.

TAKING MEASUREMENTS IS VERY IMPORTANT FOR THE CREATION OF THE MODEL.

On the MEASUREMENTS page, by selecting "Show dummy for measurements", a dummy is displayed.

Selecting a box for entering measurements, for example Person Height, indicates how to correctly take this height.

Your measurements must be entered as requested, then the TittiCad program processes them so that the original proportions of the model chosen by you fits your measurements.

THE MOD-A-49 IS COMPOSED OF FOLLOWING PARTS:

- N.1 IN FRONT. Once on the double fabric.
- N.2 BEHIND. Once on the fabric fold.
- N.3 SLEEVE. Once on the double fabric.
- N.4 CUFF. Once on the double fabric.
- N.5 FRONT BOTTOM EDGE. Once on the double fabric.
- N.6 FRONT PLATFORM. Once on the double fabric.
- N.7 PLACING AT THE BACK. Once on the fold of the fabric.
- N.8 BOTTOM EDGE BACK. Once on the SINGLE fabric.

Note:

The pattern already includes seam allowances.

MATERIAL REQUIRED FOR CREATION OF THIS MODEL

The fabric used for the model in the photo is a hemp blend linen without elastane.

- Recommended fabric: cotton, linen, wool, with or without elastane.
- QUANTITY see next page.
- Sewing machine thread.
- Snap button diameter 2 cm.
- Button applied to enrich the model.

Being a tailor-made model, it is not possible to indicate the right quantity for all the materials needed. You will have to measure them appropriately.

PATTERN ON FABRIC AND QUANTITY OF STUFF REQUIRED

There are 2 possible cases, depending on whether you are using the TittiCad Program (installed on your PC), or the Online Pattern Service (present on the website www.titticad.com):

- TittiCad program:

By opening the PRINT page and selecting the **Layout** on fabric item in the "Available Print List".

a suggestion of how to place the pattern on fabric appears.

- Online paper patterns from www.titticad.com:

After entering the measurements and requesting the Free Preview, the Arrangement on fabric and required fabric length is shown at the bottom of the page.

The vertical arrow indicates the quantity of fabric needed, while the horizontal arrow indicates the width of the fabric, it can be double fabric (when 75cm is indicated) or single fabric (when 150cm is indicated).

It is recommended to always take a little more (10-15cm)

PACKAGING TIPS

Paper pattern preparation

The Property of the Property o
How to assemble TittiCad paper pattern.
First steps in packaging
2-3 Things to know about fabric before placing paper pattern on fabric.
How to place paper pattern on fabric.
Mark the outline of the paper pattern and assemble the front and back.
Video tutorials specific to this model
MOD-A-49 Short Jacket. Complete package.
Sewing simple darts.
How to apply thermoadhesive liner.
Strap closure with button and automatic, without buttonhole

For all video tutorials on the packaging click the link below:

www.titticad.com/confezione