

DUSTER

MODEL A-14



MODEL A-14



MODEL A-14

MODEL DESCRIPTION A-14

- Dust coat with zip on the front.
- Shaping darts in front and back.
- Wide Neck.
-

False pocket

with flap.- Sleeve flared at the bottom.
- Internally margins

finished with bias tape.

For some physiques it is recommended to reduce the width of the waist darts or even ignore them if you want to have more softness.

VERY IMPORTANT FOR THE REALIZATION OF THE MODEL IS TAKING THE MEASUREMENTS.

In the MEASUREMENTS page, selecting “**Show dummy for measures**”, a dummy is displayed.

Selecting a box for entering measurements, for example Person Height, indicates how to correctly take this height.

Your Measurements must be entered as requested, then it is the TittiCad program that processes them so that the original proportions of the model chosen by you adapt to your measurements.

THE A-14 MODEL IS COMPOSED OF FOLLOWING PARTS:

N.1 FRONT. Once on the double fabric.

#2 BEHIND. Once on the fabric fold.

N.3 SLEEVE. Once on the double fabric.

N.4 NECK. Once on the fabric fold.

N.5 POCKET FLAP. Twice on double fabric.

N.6 FRONT PANEL. Once on the double fabric.

N.7 BEHIND PANEL. Once on the fabric fold.

Note:

The pattern already includes seam allowances.

MATERIAL REQUIRED FOR THE REALIZATION OF THIS MODEL

The fabric used for the model in the photo is medium weight cotton, with warp and weft threads of various thicknesses, this gives the fabric this particular effect.

- Recommended fabric: cotton gabardine, denim, cotton twill, canvas, heavy linen. •

QUANTITY see following page. • Medium weight thermo-adhesive cotton canvas, for facings. •

Double slider zipper. • 2.5 cm wide bias tape, to finish all the internal edges. (Inner edges can always be finished with an overlock stitch or a sewing machine). • Sewing machine thread.

Being a made-to-measure model, it is not possible to indicate the right quantity for all the materials required.

You must be the one to measure it appropriately.

PATTERN ON THE FABRIC AND QUANTITY OF REQUIRED CLOTH

There are 2 possible cases, depending on whether you are using the TittiCad Program (installed on your PC), or the Online Pattern Making Service (present on the website www.titticad.com):

- TittiCad program: By opening the PRINT page and selecting the **Arrangement on fabric** item from the "List of Available Prints",

a suggestion is displayed on how to position the model on the fabric.

- [Online Patterns of www.titticad.com](http://www.titticad.com): After entering the measurements and requesting the Free Preview, it is shown at the bottom of the page **Arrangement on fabric and required fabric length.**

The vertical arrow indicates the quantity of fabric required, while the horizontal arrow indicates the width of the fabric, it can be double fabric (when 75cm is indicated) or single fabric (when 150cm is indicated).

It is recommended to always take a little more (10-15 cm)

PACKAGING TIPS

Pattern preparation

[How to assemble TittiCad pattern.](#)

First steps in the packaging

[2-3 Things to know about fabric before placing pattern on fabric.](#)

[How to place pattern on fabric.](#)

[Mark the outline of the pattern and assemble a front with a back.](#)

Specific video tutorials for this model

Model A-14 is trimmed sides and shoulder as video shows:

[How to use bias tape to finish 2 parts to join.](#)

[Sew round sleeves.](#)

[Zipper on jacket.](#)

The same technique shown in the video is used to apply bias tape to the bottom of the sleeve, the bottom of the duster and around the edge of the placket: [How to apply bias tape to the bottom of the trousers.](#)

For all the video tutorials on the pack, click the link below:

www.titticad.com/package