

BLOUSE

MOD-A-59



MODEL DESCRIPTION

This model features darts at the waist and side at the front, at the waist at the back. The size of the darts at the waist for both the front and the back is free.

V-neck front finished with piping.

There is a fold at the bottom of the neckline.

Set-in sleeves, length and bottom circumference as desired.

The length of the model is as desired, taking into account that the minimum length of this model can reach up to hip height.

Attention!!! This model is created without fit in the Circumferences.

The possibility is given to add cm of wearability in the Bust Circumference, Waist Circumference and Hip Circumference.

The fit entered refers to the entire circumference and not to the individual part.

Always pay attention, after entering the measurements, that the model is harmonious.

**VERY IMPORTANT FOR THE CREATION OF THE MODEL
IT'S THE TAKING OF MEASURES.**

On the MEASUREMENTS page, by selecting “**Show dummy for measurements**”, a dummy is displayed.

Selecting a box for entering measurements, for example Person Height, indicates how to correctly take this height.

Your measurements must be entered as requested, then it is the TittiCad program that processes them so that the original proportions of the model chosen by you adapt to your measurements.

**THE MODEL IS COMPOSED OF THE FOLLOWING
SET OFF:**

N.1 IN FRONT. Once on the fabric fold.

N.2 BEHIND. Once on the fabric fold.

N.3 SLEEVE . Once on the double fabric.

N.4 FRONT EDGE. Once on the double fabric.

N.5 PLACING AT THE BACK. Once on the crease
fabric.

Note:

The pattern already includes seam allowances.

MATERIAL REQUIRED FOR CREATION OF THIS MODEL

The fabric of the model in the photo is a cotton-linen blend with 5% elastane.

- Recommended fabric: shirt cotton, linen, viscose.
- **QUANTITY** see next page. • Sewing machine thread.
- Lightweight cotton thermo-adhesive liner.

Being a tailor-made model, it is not possible to indicate the right quantity for all the materials needed.

You will have to measure them appropriately.

PATTERN ON FABRIC AND QUANTITY OF FABRIC NECESSARY

There are 2 possible cases, depending on whether you are using the TittiCad Program (installed on your PC), or the Online Pattern Service (present on the website www.titticad.com):

- TittiCad program:

By opening the PRINT page and selecting the Layout **on fabric** item in the "Available Print List".

a suggestion of how to place the pattern on fabric appears.

- [Online paper patterns from www.titticad.com](http://www.titticad.com):

After entering the measurements and requesting the Free Preview, the **Arrangement on fabric and required fabric length is shown at the bottom of the page.**

The vertical arrow indicates the quantity of fabric needed, while the horizontal arrow indicates the width of the fabric, it can be double fabric (when 75cm is indicated) or single fabric (when 150cm is indicated).

It is recommended to always take a little more (10-15 cm)

PACKAGING TIPS

Paper pattern preparation

[How to assemble TittiCad paper pattern.](#)

First steps in packaging

[2-3 Things to know about fabric before placing paper pattern on fabric.](#)

[How to place paper pattern on fabric.](#)

[Mark the outline of the paper pattern and assemble the front and back.](#)

Video tutorials specific to this model

[MOD-A-59 Blouse. Complete package.](#)

[How to apply thermoadhesive liner.](#)

[Sewing simple darts.](#)

[Sew diamond darts.](#)

[Sew set-in sleeve.](#)

[Double hem.](#)

For all video tutorials on the packaging click the link below:

www.titticad.com/confezione